

STATIC ERASER
CROSS-FLOWFAN

Model No. CF300-E

Wide Area Neutralization



Easy maintenance of electrode needles with a brush that can be slid by a finger.

Wide blow cross-flow fan and straight front cover enable superior ionizing performance.

Tel. (+33) 02 54 55 38 10 Fax. (+33) 02 54 70 81 26

AUTOMAX S.A. - Z.A. - Rue de Champ Chardon 41250 MONT PRES CHAMBORD - FRANCE E-mail: info@automax.fr www.automax.fr







Neutralization for wide area. Good for variety of applications.






Dimensions









Specifications

Model No.	CF300-E				
lonizing method	Piezoelectric high-frequency AC corona discharge				
Power supply	24VDC ±10%				
Consumption electric current	500 mA (max.)				
H×W×D mm	157×348×165				
Weight	approx. 2.9 kgs				
Fan speed	2.5m³/min(max)				
Noise level	52.5dBA (measured at 1m)				
Ozone production	0.05ppm or less				
Alarms	High voltage output stop (red LED),				
	fan locked (red LED)				
Protection function	Fan motor rotation monitoring function (Detecting rotation lock)				
	High-voltage output shut down function(overload detection)				
	Power supply fuse 3.15A				
Storage environment temperature and humidity	$5\sim40^\circ\mathrm{c}~35\sim65\%\mathrm{RH}$ (with no dew condensation or freezing)				
Storage environment					
temperature and humidity	$0\sim60^{\circ}\mathrm{c}\ 35\sim85\%\mathrm{RH}$ (with no dew condensation or freezing)				
Operating range	150 mm to 900 mm				
Installation place	Non-hazardous place indoors				
Decay time	within 1.5sec (at max.airflow,straight,measured at 300mm)				
Ion balance	within ±10V (at the time of shipment,measured at 300mm)				
Filter	Rough filter				
Material	Body, Stand : SPCC/Front cover : ABS resin				
	Electrode needles : Stainless steel				
Accessories	AC adapter AD24-IT/AC input cable1.8m/				
	Cleaning brush				

Performance





- Replacement Parts
- •Cleaning Brush CF-300B
- •Rough Filter CF-300F

automax®

ZA Champ Chardon 41250 Mont Près Chambord Tel. +33 (0)254 553 810 Fax +33 (0)254 708 126 info@automax.fr - www.automax.fr

- Product specifications, dimensions, pricing, and other information are subject to change without notice.
- Static electricity erasing capability values given in this catalog were obtained in Your results may differ depending on the operating environment.

Distributed by			